



Driver: 鶴巻 翔 Vehicle: RDX
 Event: _____ Firmware Version: _____
 Date: 20230708 Motor: G4 13.5T 品番: 30401140
 Track: らじこんひろば Endbell Timing: 40
 Surface: Pタイル 黒 Rotor: 5x12.3 30820017
 Temperature: _____ Final Ratio: スパー78 ピニオン20

Data Record	Max. ESC Temperature: <u>56</u>	Note: <u>タイヤ: TDT-002PE トップライン スポーツエディションHDPE</u>
	Max. Motor Temperature: <u>44</u>	
	Min. Battery Voltage: <u>7.2</u>	
	Max. Motor RPM: <u>93657</u>	

Type	ID	Item	Value
General Setting	1A	Running Mode	<input type="checkbox"/> Fwd/Brk <input checked="" type="checkbox"/> Fwd/Rev/Brk <input type="checkbox"/> Fwd/Rev
	1B	Reverse Force	<input checked="" type="checkbox"/> 25% <input type="checkbox"/> 50% <input type="checkbox"/> 75% <input type="checkbox"/> 100%
	1C	Reverse Delay	<u>2.0</u> (0-5S Adjustable)
	1D	Cutoff Voltage	<input type="checkbox"/> Disabled <input checked="" type="checkbox"/> Auto _____ (3.0-7.4 Adjustable)
	1E	ESC Thermal Protection	<input checked="" type="checkbox"/> Disabled <input type="checkbox"/> 105°C/221 <input type="checkbox"/> 5°C/257
	1F	Motor Thermal Protection	<input checked="" type="checkbox"/> Disabled <input type="checkbox"/> 105°C/221 <input type="checkbox"/> 5°C/257
	1G	BEC Voltage	<u>6.0</u> (5V-7.4V Adjustable)
	1H	Remote Off	<input checked="" type="checkbox"/> Disabled <input type="checkbox"/> Enabled
	1I	Motor Rotation	<input checked="" type="checkbox"/> CCW <input type="checkbox"/> CW
	1J	Phase-AC Swap	<input checked="" type="checkbox"/> Disabled <input type="checkbox"/> Enabled
Throttle Control	2A	Throttle Rate Control	<u>20</u> (1-30 Adjustable)
	2B	Throttle Curve	<input checked="" type="checkbox"/> Linear <input type="checkbox"/> Customize
	2C	Neutral Range	<u>5</u> (3%-10% Adjustable)
	2D	Initial Throttle Force	<u>1</u> (1-15 Adjustable)
	2E	Coast	<u>0</u> (0%-15% Adjustable)
	2F	Drive Frequency	<input type="checkbox"/> 1K <input type="checkbox"/> 2K <input type="checkbox"/> 4K <input type="checkbox"/> 8K <input checked="" type="checkbox"/> 12K <input type="checkbox"/> 16K <input type="checkbox"/> 24K <input type="checkbox"/> 32K <input type="checkbox"/> 40K <input type="checkbox"/> 48K <input type="checkbox"/> Customize
	2G	Softening Value	<u>0</u> (0-30° Adjustable)
	2H	Softening Range	<u>0</u> (0%-75% Adjustable)
Brake Control	3A	Drag Brake	<u>5</u> (0%-100% Adjustable)
	3B	Brake Force	<u>100</u> (0%-100% Adjustable)
	3C	Initial Brake Force	<input checked="" type="checkbox"/> =Drag Brake _____ (0%-50% Adjustable)
	3D	Brake Rate Control	<u>10</u> (1-20 Adjustable)
	3E	Brake Curve	<input checked="" type="checkbox"/> Linear <input type="checkbox"/> Customize
	3F	Brake Frequency	<input checked="" type="checkbox"/> 0.5K <input type="checkbox"/> 1K <input type="checkbox"/> 2K <input type="checkbox"/> 4K <input type="checkbox"/> 8K <input type="checkbox"/> 12K <input type="checkbox"/> 16K <input type="checkbox"/> 20K <input type="checkbox"/> 24K <input type="checkbox"/> Customize
Timing	4A	Boost Timing	<u>48</u> (0-64° Adjustable)
	4B	Timing Activation	<input checked="" type="checkbox"/> RPM <input type="checkbox"/> Auto
	4C	Boost Start RPM	<u>8000</u> (500-35000RPM Adjustable)
	4D	Boost End RPM	<u>45000</u> (3000-60000RPM Adjustable)
	5A	Turbo Timing	<u>0</u> (0-64° Adjustable)
	5B	Turbo Delay	<input checked="" type="checkbox"/> Instant _____ (0.05-1.0S Adjustable)
	5C	Turbo Increase Rate	<input type="checkbox"/> 3 <input type="checkbox"/> 6 <input type="checkbox"/> 9 <input type="checkbox"/> 12 <input type="checkbox"/> 15 <input type="checkbox"/> 18 <input checked="" type="checkbox"/> 21 <input type="checkbox"/> 24 <input type="checkbox"/> 27 <input type="checkbox"/> 30 <input type="checkbox"/> Instant
5D	Turbo Decrease Rate	<input type="checkbox"/> 3 <input type="checkbox"/> 6 <input type="checkbox"/> 9 <input type="checkbox"/> 12 <input type="checkbox"/> 15 <input type="checkbox"/> 18 <input type="checkbox"/> 21 <input type="checkbox"/> 24 <input checked="" type="checkbox"/> 27 <input type="checkbox"/> 30 <input type="checkbox"/> Instant	