



Driver: JIN SAWADA      Vehicle: INFINITY IF14-2  
 Event: TITC2023      Firmware Version: \_\_\_\_\_  
 Date: 2023-2-26      Motor: HW 4.5T  
 Track: INFINITY ADDICT CIRCUIT      Endbell Timing: 34  
 Surface: Ashalt      Rotor: STD  
 Temperature: 36      Final Ratio: 7.23

Data Record	Max. ESC Temperature: _____	Note: _____ _____ _____
	Max. Motor Temperature: _____	
	Min. Battery Voltage: _____	
	Max. Motor RPM: _____	

Type	ID	Item	Value
General Setting	1A	Running Mode	<input checked="" type="checkbox"/> Fwd/Brk <input type="checkbox"/> Fwd/Rev/Brk <input type="checkbox"/> Fwd/Rev
	1B	Reverse Force	<input checked="" type="checkbox"/> 25% <input type="checkbox"/> 50% <input type="checkbox"/> 75% <input type="checkbox"/> 100%
	1C	Cutoff Voltage	<input checked="" type="checkbox"/> Disabled <input type="checkbox"/> Auto    _____ (3.0-7.4 Adjustable)
	1D	ESC Thermal Protection	<input checked="" type="checkbox"/> Disabled <input type="checkbox"/> 105°C/221 <input type="checkbox"/> 125°C/257
	1E	Motor Thermal Protection	<input checked="" type="checkbox"/> Disabled <input type="checkbox"/> 105°C/221 <input type="checkbox"/> 125°C/257
	1F	BEC Voltage	<u>6.8</u> (5V-7.4V Adjustable)
	1G	Remote Off	<input checked="" type="checkbox"/> Disabled <input type="checkbox"/> Enabled
	1H	Sensor Mode	<input checked="" type="checkbox"/> Full Sensored <input type="checkbox"/> Sensored/Sensorless Hybrid
	1I	Motor Rotation	<input checked="" type="checkbox"/> CCW <input type="checkbox"/> CW
	1J	Phase-AC Swap	<input checked="" type="checkbox"/> Disabled <input type="checkbox"/> Enabled
Throttle Control	2A	Throttle Rate Control	<u>20</u> (1-30 Adjustable)
	2B	Throttle Curve	<input checked="" type="checkbox"/> Linear <input type="checkbox"/> Customize
	2C	Neutral Range	<u>6</u> (3%-10% Adjustable)
	2D	Initial Throttle Force	<u>3</u> (1-15 Adjustable)
	2E	Coast	<u>0</u> (0%-15% Adjustable)
	2F	Drive Frequency	<input type="checkbox"/> 1K <input type="checkbox"/> 2K <input type="checkbox"/> 4K <input checked="" type="checkbox"/> 8K <input type="checkbox"/> 12K <input type="checkbox"/> 16K <input type="checkbox"/> 24K <input type="checkbox"/> 32K <input type="checkbox"/> Customize
	2G	Softening Value	<u>30</u> (0-30° Adjustable)
	2H	Softening Range	<u>50</u> (0%-75% Adjustable)
Brake Control	3A	Drag Brake Force	<u>14</u> (0%-100% Adjustable)
	3B	Drag Brake Rate	<input checked="" type="checkbox"/> Auto    _____ (1-20 Adjustable)
	3C	Max. Brake Force	<u>88</u> (0%-150% Adjustable)
	3D	Brake Rate Control	<u>20</u> (1-20 Adjustable)
	3E	Brake Frequency	<input type="checkbox"/> 0.5K <input type="checkbox"/> 1K <input checked="" type="checkbox"/> 2K <input type="checkbox"/> 4K <input type="checkbox"/> 8K <input type="checkbox"/> 12K <input type="checkbox"/> 16K <input type="checkbox"/> Customize
	3F	Brake Control	<input checked="" type="checkbox"/> Linear <input type="checkbox"/> Traditional <input type="checkbox"/> Hybrid
Timing	4A	Boost Timing	<u>6</u> (0-64° Adjustable)
	4B	Timing Activation	<input checked="" type="checkbox"/> RPM <input type="checkbox"/> Auto
	4C	Boost Start RPM	<u>7500</u> (500-35000RPM Adjustable)
	4D	Boost End RPM	<u>22500</u> (3000-60000RPM Adjustable)
	5A	Turbo Timing	<u>36</u> (0-64° Adjustable)
	5B	Turbo Delay	<input type="checkbox"/> Instant <u>0.1</u> (0.05-1.0S Adjustable)
	5C	Turbo Increase Rate	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 5 <input type="checkbox"/> 8 <input type="checkbox"/> 12 <input type="checkbox"/> 16 <input checked="" type="checkbox"/> 20 <input type="checkbox"/> 25 <input type="checkbox"/> 30 <input type="checkbox"/> Instant
5D	Turbo Decrease Rate	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 5 <input type="checkbox"/> 8 <input type="checkbox"/> 12 <input type="checkbox"/> 16 <input type="checkbox"/> 20 <input checked="" type="checkbox"/> 25 <input type="checkbox"/> 30 <input type="checkbox"/> Instant	