

Driver: 石川まひろ Vehicle: _____
 Event: 袖ヶ浦スタジアム月例レース Firmware Version: _____
 Date: 2022/03/13 Motor: G3R21.5T/ROAR
 Track: 袖ヶ浦スタジアム Endbell Timing: 45
 Surface: _____ Rotor: 30820417 7x12.2チタン
 Temperature: _____ Final Ratio: 4.99



Data Record	Max. ESC Temperature: <u>66</u>	Notes
	Max. Motor Temperature: <u>77</u>	
	Min. Battery Voltage: <u>7.36</u>	
	Max. Motor RPM: <u>33303</u>	

Am0 - PetitRC

Type	Item	Value										
General Setting	Running Mode	<input checked="" type="checkbox"/> Fwd/Brk	Fwd/Rev/Brk		Fwd/Rev							
	Reverse Force	<input checked="" type="checkbox"/> 5%	50%	75%	100%							
	Cutoff Voltage	<input checked="" type="checkbox"/> Disabled	Auto	_____		(3.0-7.4 Adjustable)						
	ESC Thermal Protection	<input checked="" type="checkbox"/> 05°C/221°F	125°C/221°F		Disabled							
	Motor Thermal Protection	<input checked="" type="checkbox"/> 05°C/221°F	125°C/221°F		Disabled							
	BEC Voltage	<u>7.0</u> (5V-7.4V Adjustable)										
	Remote Off	Enabled	<input checked="" type="checkbox"/> Disabled									
	Sensor Mode	<input checked="" type="checkbox"/> Full Sensored	Sensored/Sensorless Hybrid									
	Motor Rotation	<input checked="" type="checkbox"/> CCW	CW									
Throttle Control	Throttle Rate Control	<u>30</u> (1-30 Adjustable)										
	Throttle Curve	<input checked="" type="checkbox"/> Linear	Customize									
	Neutral Range	4%	<input checked="" type="checkbox"/> 6%	8%								
	Coast	<u>0</u> (0%-20% Adjustable)										
	Drive Frequency	1K	2K	<input checked="" type="checkbox"/> 4K	8K	12K	16K	24K	32K	Customize		
	Softening Value	_____ (0-30° Adjustable)										
	Softening Range	<u>0</u> (0%-75% Adjustable)										
Brake Control	Drag Brake	<u>0</u> (0%-100% Adjustable)										
	Brake Force	<u>100</u> (0%-150% Adjustable)										
	Initial Brake Force	=Drag Brake	<u>0</u> (0%-50% Adjustable)									
	Brake Rate Control	<u>20</u> (1-20 Adjustable)										
	Brake Curve	<input checked="" type="checkbox"/> Linear	Customize									
	Brake Frequency	1K	<input checked="" type="checkbox"/> 2K	4K	8K	16K	Customize					
	Brake Control	<input checked="" type="checkbox"/> Linear	Traditional			Hybrid						
Timing	Boost Timing	<u>45</u> (0-64° Adjustable)										
	Timing Activation	RPM	<input checked="" type="checkbox"/> Auto									
	Boost Start RPM	_____ (500-35000RPM Adjustable)										
	Boost End RPM	_____ (3000-60000RPM Adjustable)										
	Turbo Timing	<u>27</u> (0-64° Adjustable)										
	Turbo Delay	<input checked="" type="checkbox"/> Instant	_____ (0.05-1.0S Adjustable)									
	Turbo Increase Rate (deg/0.1sec)	3	6	9	12	15	18	21	<input checked="" type="checkbox"/> 24	27	30	Instant
	Turbo Decrease Rate (deg/0.1sec)	3	6	9	12	15	<input checked="" type="checkbox"/> 18	21	24	27	30	Instant